TGR 1846 (4x2) ELG TRACTOR, HIGH ROOF

BMC

BMC

0.0

0





TURQUALITY

6

CABIN

TYPF High Roof, Sleeper Cab BUNK CAB SUSPENSION Air

ENGINE

6

BRAND / MODEL FPT Cursor 11 ENT VI (Euro 6) TYPF Turbo Intercooler Diesel NUMBER OF CYLINDERS

DISPLACEMENT

11.1 L MAXIMUM POWER 460 PS (338 kW) @ 1900 rpm MAXIMUM TORQUE 2150 Nm @ 1050-1550 rpm DIAMETER & STROKE 125 mm/ 140 mm

TANKS

FUEL TANK CAPACITY 6001 ADBLUE TANK CAPACITY 80 L

GEAR BOX

BRAND / MODEL ZF 12 TX 2210 TO (Automated) [S] ZF 12 TX 2211 TO (Automated +Intarder) [0] NUMBER OF GEARS 12 Forward, 2 Reverse GEAR RATIO 12.9 - 0.7 (Reverse: 12.03 - 9.29) CLUTCH 430 mm, Single Disc

AXLES

FRONT AXLE LOAD CAPACITY 7500 ka REAR AXLE Diff. Number of Speeds Single Speed Gear Ratio 3.08:1 LOAD CAPACITY 13000 kg

SUSPENSION

FRONT AXLE Parabolic Springs, Telescopic Shock Absorbers REAR AXLE Air Bellows, Telescopic Shock Absorbers ANTI-ROLL BAR Rear and Front Axles

TYRES

SIZE / NUMBER	
295 / 80 R 22.5 , 6+1	
(5th Wheel Height: 1150/1200)	[S]
315 / 70 R 22.5 , 6+1	
(5th Wheel Height: 1050/1100/1150/1200)	[0]

RIMS

SIZE 8.25 x 22.5

PERFORMANCE

TOP SPEED (LIMITED) (km/h) 90 TURNING RADIUS (m) 69

ELECTRICAL SYSTEM

VOI TAGE 24 V BATTERIES 2 x 12 V / 180 Ah ALTERNATOR 120 A STARTER MOTOR 24 V

STEERING SYSTEM

TYPE Hvdraulic

BRAKE SYSTEM

BRAKE SYSTEM TYPE Air Operated Dual Circuit Type Ø430x45 Disc Brakes, EBS, ESC, LDWS, AEBS RETARDER TYPE Intarder (600 kW) [0] ENGINE BRAKE 372 kW [S]

CHASSIS

CHASSIS PROFILE High Strength Steel, 8mm

STANDARD ACCESSORIES

DIMENSIONS (mm) A: Wheelbase

F: Useful Chassis Length

B: Overall Length

D: Overall Height

I: Inner Height

Automatically Operated Digital Air Conditioner (6 kW) 7" Multimedia Display 2 USB + Cigarette Lighter (Driver Side) 2 USB + 12V (Passenger Side), 1 USB (Multimedia)

C: Overall Width (Excluding Mirrors)

Elektronic Brake System (EBS) Elektronic Stability Control (ESC) Active Emergency Brake System (AEBS) Immobilizer Single Key with Remote Control and Central Locking Differential Lock Digital Tachograph Electrically Operated Windows Air Suspended Driver Seat Adjustable Driver Seat Armrest Seat Headrest Seatbelt Sensor (Driver) Driver and Passenger Sun Visor Dry Type Cab Heater (2 kW) Hill-holder Assist Pad Wear Indicator Catwalk Roof & Side Spoiler Lane Departure Warning System (LDWS) Axle Load Indicator Spare Wheel Front Fog Lamps Electrically Operated Headlight Leveling Trailer Side Lamp Lamp Under Hood Lamp Under Cab Flectric Cab Lift Fleet Management System Socket and Module Tyre Inflation Valve High-end Dashboard with Digital Cluster Refrigerator (55lt)

OPTIONAL ACCESSORIES

H: Front Track

J: Rear Track

R: Inner Width

S: First Step Height

K': Chassis Height

5th Wheel Height:

2 USB (Sleeper Area)

Cruise Control

4 Points Independent Air Cab Suspension

Electrically Operated and Heated Side Mirrors

Steering Wheel With Multimedia,

Adjustable Steering Column

Electrically Operated Sunroof

Speed and Menu Control Buttons [3]

ADR Package Intarder (600 kW) Speed Limiter (for Intarder Version) [4] Adjustable Passenger Seat Armrest Driver Seat with Air Operated Back Support Heated Driver Seat Transmission PTO 5th Wheel Options: 1050, 1100, 1150, 1200 [2] Aluminum Rim Tire Pressure Monitoring System Auxiliary Fuel Tank (300 lt) [5] 225 Ah Battery [5] Low Profile Bumper

2100

1835


418


2155

1200

911

К'
Ô
-







0: Front Overhang G': Rear Overhang

WEIGHTS (kg)



3700

5965

2545

1950

(Tunnel Height: 190)

1440

825

3577 (3935 SP)

3470 (3310 SP)

All visuals, dimensions, characteristics and equipment are for information purposes only they are not contractual. BMC reserves the right to modify them without prior warning (February 2021).

BMC OTOMOTIV SANAYI VE TİCARET A.Ş.