TGR 1832 (4x2) L ROAD TRUCK



BMC

TURQUALITY

CABIN

TYPF

Day Cab

CAB SUSPENSION

Mechanical

ENGINE

BRAND / MODEL

Cummins ISB6.7 (Euro 6)

TYPE

Turbo Intercooler Diesel

NUMBER OF CYLINDERS

DISPLACEMENT

MAXIMUM POWER

320 PS (233 kW) @2300 rpm

MAXIMUM TOROUE

1200 Nm @ 1100 rpm

DIAMETER & STROKE

107 mm / 124 mm

TANKS

FUEL TANK CAPACITY

300 L (S)

405 L (0)

ADBLUE TANK CAPACITY

GEAR BOX

BRAND / MODEL

ZF 9 S (Manual)

NUMBER OF GEARS

9 Forward, 1 Reverse

GEAR RATIO

12.73:1; 1.00:1 (Reverse 12.04:1)

CLUTCH

430 mm, Single Disc

AXLES

FRONT AXLE LOAD CAPACITY

7500 kg

REAR AXLE

Diff. Number of Speeds

Single Speed

Gear Ratio 4331

LOAD CAPACITY

13000 kg

SUSPENSION

FRONT AXLE

Semi-elliptical Springs, Telescopic Shock Absorbers

REAR AXLE

Semi-elliptical Springs,

Telescopic Shock Absorbers

ANTI-ROLL BAR

Rear (2nd) and Front (1st) Axles

TYPFS

SIZE / NUMBER

315 / 80 R 22.5, 6+1 [S] 315 / 70 R 22.5 , 6+1 **[0]** 315 / 60 R 22.5 , 6+1 [0]

RIMS

SIZE

9 x 22.5

PERFORMANCE

TOP SPEED (LIMITED) (km/h)

TURNING RADIUS (m)

ELECTRICAL SYSTEM

VOLTAGE

24 V

BATTERIES

2 x 12 V / 180 Ah

ALTERNATOR

STARTER MOTOR

STEERING SYSTEM

TYPF

Hydraulic

BRAKE SYSTEM

BRAKE SYSTEM TYPE

Air Operated Dual Circuit Type Disc Brakes,

EBS, ESC, AEBS, LDWS

RETARDER TYPE

Electromagnetic (360 kW) [0]

ENGINE BRAKE

Engine Brake

CHASSIS

CHASSIS PROFILE

"C" Section Steel, 8mm

STANDARD ACCESSORIES

Manually Operated Digital Air Conditioner (6 kW)

Radio / MP3 / Bluetooth

2 USB + Cigarette Lighter (Driver Side)

2 USB + 12V (Passenger Side), 1 USB (Multimedia) 4 Points Independent Mechanic Cab Suspension

Cruise Control

Electrically Operated and Heated Side Mirrors

Adjustable Steering Column Manually Operated Sunroof

Electronic Brake System (EBS)

Electronic Stability Control (ESC)

Lane Departure Warning System (LDWS)

Immobilizer

Single Key with Remote Control and Central Locking

Differential Lock Digital Tachograph

Electrically Operated Windows

Air Suspended Driver Seat

Seat Headrest

Seatbelt Sensor (Driver)

Driver and Passenger Sun Visor

Hill-holder Assist

Adjustable Driver Seat Armrest

Pad Wear Indicator

Active Emergency Brake System (AEBS)

Spare Wheel Front Fog Lamps

Electrically Operated Headlight Leveling

1 (Driver) + 2 (Passenger) Seat Configuration

Lamp Under Hood Lamp Under Cab

Tyre Inflation Valve

Body Structure Module

OPTIONAL ACCESSORIES

7" Multimedia Display

Driver Seat with Air Operated Back Support

Heated Driver Seat

Adjustable Passenger Seat Armrest

Fleet Management System Socket and Module

4 Points Independent Air Cab Suspension

Electric Cab Lift Aluminum Rim

Electrically Operated Sunroof

Tire Pressure Monitoring System

ADR Package

Retarder

Front Dust Protection

315/60 Tyre Option

315/70 Tyre Option

Transmission PTO 410 lt Aluminum Fuel Tank

Dry Type Additional Heater (2 kW)

Smart Tachograph

Rear Towing Hook (Drawbar Type)

Rear Towing Hook (Central Axle Type)

Heated Windshield MTCO - Type 1324 Tachograph


H: Front Track

J: Rear Track

P. Inner Width

S: First Step Height

K': Chassis height



WEIGHTS (kg)

*For kerb weight calculation, minimum equipment, no driver, 20 liters of fuel, 5 liters of urea included. Kerb weight may change depends on optional equipments Y250 Z255 (Looded) 101. Options [8]. Standard

DIMENSIONS (mm)

A: Wheelbase

4250

B: Overall Length C: Overall Width (Excluding Mirrors) D: Overall Height

2545 3275 6530

8815

(Tunnel Height: 190)

1440

2990

F: Useful Chassis Length I: Inner Height 1670

G': Rear Overhang

0: Front Overhang

MAXIMUM WEIGHT LOADED FRONT AXLE MAXIMUM WEIGHT LOADED REAR AXLE **GROSS VEHICLE WEIGHT**

TECHNICAL 7500 13000 18000

LEGAL 7500 11500

18000

KERB WEIGHTS (kg) 1. AXLE 2. AXLE

TOTAL

4280 2175 6455*

2083

1838

492

2155

1155

BMC reserves the right to change the technical specifications of the products without prior notice (April 2024)

BMC OTOMOTIV SANAYI VE TİCARET A.Ş.

444 9 262

